



| Pos | Part Number | Description | Additional Text | Quantity |
|-----|-------------|--------------------------------|-----------------|----------|
| 1 | 0912060203 | AH SCREW DIN0912-M 6X20 | | 1.00 |
| 2 | 54637067000 | SPRING SLEEVE | | 1.00 |
| 3 | 54637066000 | OVERLOAD SPRING | | 1.00 |
| 4 | 54637065000 | CONTROL LEVER WITH BALL TYPE | | 1.00 |
| 5 | 54637068100 | BUSHING SLEEVE | | 1.00 |
| 6 | 50437065044 | SLOTTED LEVER R/S | | 1.00 |
| 7 | 50437064044 | SLOTTED LEVER L/S | | 1.00 |
| 8 | 0019050106S | hex lobe countersunc screw M5x | | 2.00 |
| 9 | 50437079000 | LOCK PLATE | | 2.00 |
| 10* | 50437023100 | exhaust flap bushing | | 2.00 |
| 11 | 50437061044 | CONTROLLER DRUM CPL. | | 2.00 |
| 12 | 0770140201 | O-RING 14X2 FPM 75SH | | 4.00 |
| 14* | 50537020000 | Control flap | | 1.00 |
| 16 | 50437085000 | STOP PLATE | | 1.00 |
| 17 | 0912060163 | AH SCREW DIN0912-M 6X16 | | 1.00 |
| 18 | 0014050123 | HH COLLAR SCREW M 5X12 WS=6 | | 1.00 |
| 22 | 0760082472 | SHAFT SEAL RING 8X24X7 A DUO | | 1.00 |
| 23 | 0625160020 | BALL BEARING 16002 C3 | | 1.00 |

| | | | | |
|-----|-------------|--------------------------------|--|------|
| 24* | 50537050144 | Centrifugal force unit | | 1.00 |
| 25 | 54637098100 | Grooved ball bearing 626LLBC3/ | | 1.00 |
| 26 | 50437057100 | ADJUSTING LEVER 125/150 2016 | | 1.00 |
| 27 | 0618101410 | needle sleeve HK 1010 10x14x10 | | 2.00 |
| 28 | 0988101610 | SHIM WASHER DIN988 10X16X1 | | 1.00 |
| 29 | 47237056000 | angle lever | | 1.00 |
| 30 | 0349000050 | WASHER DIN7349-5X15X2 | | 1.00 |
| 31 | 50437095044 | CONNECTING ROD CPL. | | 1.00 |
| 32 | 54637071200 | SPRING INSERT | | 1.00 |
| 33 | 50437069050 | SUPPORT SPRING | | 1.00 |
| 34 | 54837069000 | ADJUST. SPRING 2003 | | 1.00 |
| 35 | 0770021120 | O-RING 12,37X2,62 NBR70 | | 1.00 |
| 36 | 54837075000 | SPRING GUIDE 250/300 | | 1.00 |
| 37 | 0770240020 | O-RING 24,00X2,00 NBR70 | | 1.00 |
| 38 | 54637070100 | COVER LID 250-380'98 | | 1.00 |
| 39 | 0014050203 | HH COLLAR SCREW M 5X20 WS=6 | | 2.00 |
| 40 | 50237195055 | SECURING DIN-71805-S-8 | | 1.00 |

* = New part